Post Office Box 80504 Rancho Santa Margarita, CA 92688-0504 Tel: (866) 520-0094 Fax: (877) 635-3282

Page 1 of 2 Friday, January 30, 2015

Product Specification Guide

Product: All Models, 1.5 gpm "Jet-Stream Showerhead®

Warranty: Twenty Years Limited Replacement Warranty, not subject to abuse or misuse. Product life expectancy is 30

<mark>years or more.</mark>

Rating: Water & Energy Efficient Rated Upper 1% Of Class (all showerheads). Lowest Flow (1.5 gpm) & Highest

User Acceptance (96%)

Discounts: Quantity Discounts Available

Terms: Payment Terms Are Net 10 Days, After Receipt Of Merchandise and we accept for payment Visa, MasterCard and Discover Card. On approved credit, financing is available for large orders with monthly positive cash flow for up to 36 months, 25% Deposit Required. Purchase Directly Online www.Jet-StreamShowerhead.net

Shipment: Normally within ten (10 working days, large orders 30 - 120 days; the purchaser pays surface freight costs. Specifications: The new and improved, 1.5 gpm "Jet-Stream Showerhead® is precision engineered to reduce shower-related utility (water, sewer & heated water) consumption 40% to 75% when compared to low flow or water saver (2.5-gpm) rated showers! It is the 1.5 gpm (+/- 2%) constant-volume showerhead at all residential water pressures between 20-psi and 120-psi, is Self-Cleaning, Maintenance Free and carries a 20-Year Warranty.

Simple Test: In less than 1-Minutes, the 40% minimum shower water saving is easily proven using a bucket of any size as follows:

- 1. Before installing the 1.5 gpm "Jet-Stream" Showerhead®, turn on the current shower and adjust hot and cold-water valves all the way open for the maximum flow fate of the shower and feel the pressure of the current shower with your hand.
- 2. Place the bucket under the shower and capture all of the water for 30 seconds. If uncertain of the results, repeat the test and have a second person use the watch to time the test. Document the water output volume, pressure, feel, etc.
- 3. After installing the 1.5 gpm "Jet-Stream" Showerhead[®], run the same test, for the same length of time and see and feel the pressure difference and determine the water & energy savings percentage. If the bucket is only half of the precious test, the savings is 50%. Document the water output volume, savings, pressure, feel, etc and the saving percentage on the form provided on the obverse and faxback toll-free to 1(877) NFL-DATA [635-3282].

Note! If you have not replaced showers in the past two years with water-saver (2.5 gpm) showers, the estimated savings on shower water utility consumption is 50% or more.

Features & Benefits

- Patented Technology (no restrictors), Performance & Satisfaction Guaranteed (96% user acceptance)
- Self-Cleaning, Maintenance Free (reduced maintenance & replacement costs)
- 20-Year Replacement Warranty and made of Chrome-Plated Brass, All Models (durable)
- Payback Normally Less Than 12 Months In Shower Related Utility Savings

K. H. "Skip" Haynes, Inventor & Patent Holder Since 1978

E-mail: Showerheadman@cox.net

2-Minute Installation Guide

Any Problems, Call Toll-Free (866) 520-0094

Page 2 of 2

Friday, January 30, 2015

The Rated In The Upper 1% Of Its Class 1.5 gpm "Jet-Stream" Showerhead[®] fits all standard ½-inch threaded shower arms (Adaptors are available to retrofit obsolete ball-type shower arms).

- 1. Remove the current showerhead from the shower arm extension, by hand or by using a crescent or pipe wrench.
- 2. Remove all grime or dirt from the shower arm extension with a damp rag or cloth. Wrap with plumbing tape if necessary to provide a smooth and clean connection. If needed, start the plumbing tape. 2-3 turns from the end to prevent tape cutoff.
- 3. Rated In The Upper 1% Of Its Class, The **1.5 gpm "Jet-Stream" Showerhead**® and make sure the black seal/control valve is centered in the top of the connector before installing, turning the connector clockwise by hand until snug.

Caution: Do not over-tighten as this may damage the Patented seal/control valve and cause loud "ringing" in the pipes.

Turn on the water and insure there a no leaks. Tighten as necessary by hand or with a wrench. Do not over-tighten as damage to the seal/valve may occur and the showerhead will not function as designed.

If you need assistance in making the calculations for gallons per minute, just Go To Internet: http://www.Jet-StreamShowerhead.net/calc.html and enter the information, bucket size and how long it takes to fill the bucket.

Complete & Return The Form Below Within 10 Days Via Toll-Free Fax to: 1(877) NFL-DATA [635-3282] Please Print or Type

Date:					
Name/Title:			/		
E-Mail:					
Company:					
Address:					
City/St/Zip:					
Tel:			Fax:		
Cellular:					
Total # Showers	:				
Current Shower	Test Results Infor	<mark>mation:</mark>			
			Gallons	Fill Time	Gallons
Manufacturer's	Name	Model No.	Bucket Size	(Min/Sec)	Per/Min
How do you feel	about the savings.	pressure, effectiveness, quali	fv and performan	ce of the current	t shower?
220 // do j ou 2002	□ Excellent □ Good		□ Fair		
1.5 "Jet-Stream"	"Showerhead Test	Results Information:			
			Gallons	Fill Time	Gallons
Manufacturer's	Name	Model No.	Bucket Size	(Min/Sec)	Per/Min
Jet-Stream Mfg,					
Comments (Pres	ssure/Feel)				
	avings is:		***		
How do you per Showerhead®?	rsonally feel about	the savings, pressure, effecti	veness, qualify an	d performance	of the 1.5 gpm "Jet-Str
	☐ Excellent	\Box Good	□ Fair	□ P o	or

Complete & Return This Form Within 10 Days Via Toll-Free Fax to: 1(877) NFL-DATA [635-3282]

Web Site: www.Jet-StreamMfg.com